Yantai Longcai Advanced Materials Co.,Ltd

CongCester®

File Title: Polyester resin material safety data sheet

File code: 20160129

MATERIAL SAFETY DATA SHEET

Print date: 29/01/2016

1. IDENTIFICATION

PRODUCT DETAILS

PRODUCT NAME: LC-964

TRADE NAME: LC-964

PRODUCT USE: Powder coatings

MANUFACTURER: Yantai Longcai Advanced Materials Co., Ltd

ADDRESS: 18 Hangzhou Rd, Haiyang Development Zone, Haiyang 265100, P. R. China

TELEPHONE NUMBER: +86-535-6919139

FAX NUMBER: +86-535-6919129

2. COMPOSITION/INFORMATION ON INGREDIENTS

REPORTABLE COMPONENTS:

CAS NUMBER	INGREDIENTS	WEIGHT PERCENT
121-91-5	Isophthalic acid	≤1%

3. HAZARDS IDENTIFICATION:

·GHS LABEL ELEMENT: NO

POTENTIAL HEALTH EFFECTS:

Inhalation Effects:

Exposure to dust or fume may cause irritation of the respiratory tract. May result in nasal discharge and nosebleeds, coughing, sore throat and labored breathing.

Eye Contact:

May cause moderate eye irritation.

Skin Contact:

Contains a component which is a known or suspected skin sensitizer.

4. FIRST AID MEASURES

EYES: In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

SKIN: In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. If irritation persists, get medical attention. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean contaminated shoes.

INGESTION: If swallowed, get medical attention immediately. Do not induce vomiting.

INHALATION: If affected by inhalation, move victim to fresh air. If symptoms persist, seek medical attention.

NOTE TO PHYSICIANS: No data is available.

CongCester®

Yantai Longcai Advanced Materials Co.,Ltd File Title: Polyester resin material safety data sheet File code: 20160129

5.FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, foam and / or water fog.

FIREFIGHTING INSTRUCTIONS: Water spray maybe ineffective. Water may be used to cool closed containers. If water is used, fog nozzles are preferable. However, when fighting chemical fires, self-contained breathing apparatus and protective clothing is recommended.

UNUSUAL FIRE AND EXPLOSION HAZARD: Dust control and good housekeeping are required. The dust in the air may ignite explosively. When exposed to extreme heat, it may produce harmful ingredients. Dust may also carry a static charge. Make sure equipment and personnel are grounded to avoid static discharge.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Wear appropriate protective clothing to prevent skin contact. Wear appropriate respirator when ventilation is inadequate. Avoid breathing vapors of this product. Avoid contact with skin and eyes. Avoid all possible sources of ignition (spark or flame). Keep unnecessary people away from spill area. Clean up spills immediately. Absorb with liquid-binding material (sand, diatomite, universal binders, or spill kit).Place in suitable clean, dry containers for disposal by approved methods.

LARGE SPILL: Do not clean-up or dispose except under supervision of a specialist. Eliminate all ignition sources. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Keep unnecessary people away from spill area. Follow company spill response procedures. Clean up spills immediately. Wear protective eyeglasses or chemical safety goggles and face protection. Contact lenses are not protection devices. Appropriate eye protection must be worn instead of, or in conjuction with contact lenses. Wear MSHA/NIOSH approved self-contained breathing apparatus or equivalent and full protective gear. Wear appropriate protective clothing to prevent skin contact. Place spilled material in an appropriate container for disposal. Dispose of according to all federal, state and local applicable regulations.

7. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Avoid contact with eyes, skin and clothing. Avoid breathing dust. Wash thoroughly after handling. Ground and bond containers when transferring material to prevent dust explosion. Minimize dust generation and accumulation.

SUITABLE CONTAINER: Checked all containers are clearly labeled and free from leaks.

STORAGE INCOMPATIBILITY: Avoid storage with oxidizers.

STORAGE REQUIREMENTS: The resin should be stored in the original, unopened and undamaged containers in a dry place at storage temperatures between -6° and 90°F. Exposure to direct sunlight should be avoided.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

烟台龍彩新材料有限公司

DISCRETION ADVICED: Yantai Longcai Advanced Materials Co., Ltd takes no responsibility for determining what measures are required for personal protection in any specific application. The general information given should be used with discretion.

ENGINEERING CONTROLS: Ventilation equipment should be explosion proof. Curing ovens should be properly vented to prevent release of curing off gases into the workplace. **PERSONAL PROTECTION**:



RESPIRATORY PROTECTION: Required for dusts and fume conditions.

SKIN PROTECTION: Use neoprene or other nonporous gloves. Neoprene or plastic apron and protective clothing covering exposed skin areas.

0

EYE PROTECTION: Avoid contact with eyes. Wear goggles if there is a likelihood of contact with eyes. Eyewash stations and safety showers should be readily available in handling areas. Use safety eyewear with perforated side shields.

HYGIENIC PRACTICES: Wash hands thoroughly before eating and using washroom. Remove contaminated clothing immediately and do not wear again until it has been properly laundered.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Granu	lar solid	
COLOR: Transparen	t	
ODOR: No odor		
MELTING POINT: NO	T APPLICABLE	
BOILING POINT: NOT	APPLICABLE	
FIRE POINT:NOT APP	LICABLE	
SPECIFIC GRAVITY:	1.18g/cm ³	
SOLID CONTENT: 100	0.0 %	

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY (CONDITIONS TO AVOID): Avoid exposure to sparks, open flame, hot surfaces, and all sources of heat and ignition. May produce hazardous fumes when heated to decomposition as in welding. Fumes may contain carbon monoxide, carbon dioxide, and oxides of nitrogen.

INCOMPATIBILITY: None Known.

HAZARDOUS POLYMERIZATION: Will not occur

STABILITY: This product is stable.

Yantai Longcai Advanced Materials Co.,Ltd

File Title: Polyester resin material safety data sheet

CongCester®

File code: 20160129

11. TOXICOLOGICAL INFORMATION

Not available. Refer to individual constituents.

Unless otherwise specified data extracted from raw material suppliers

Acute oral toxicity (LD50): >5000 mg/kg [Rat]. (Isophthalic acid)

Acute dermal toxicity (LD50): >2000 mg/kg [Rat]. (Isophthalic acid)

12. ECOLOGICAL INFORMATION

No data. Refer to data for ingredients.

Unless otherwise specified data extracted from raw material suppliers.

As the product is practically insoluble in water, it is separated in almost any filtration and sedimentation process.

Not biodegradable.

No bioaccumulation potential.

13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations



14. TRANSPORT INFORMATION

IMDGPAGE NUMBER: Not available

INTERNATIONAL TRANSPORT REGULATIONS: Not available

LABELS REQUIRED: Not available

SEATRANSPORTATION CONTAMINANT: No

15. REGULATORY INFORMATION

European Economic Area (including EU): this product is compliant with the registration of the REACH Regulation (EC) No. 1907/2006 as all its components are either excluded, exempt, pre-registered and/or registered.

16. OTHER INFORMATION

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Longcai assumes no obligation or liability for use of this information

Release MSDS department: Technical department

Contact Point: Yajing Yu

Abbreviation:

IMDG: International Maritime Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals